

# 4.0 REQUEST data sheet for Overspeed Governor

## STANDARD

EN 81-20/50 Version 20-02



Request no. \_\_\_\_\_ Delivery date: \_\_\_\_\_ Quantity: \_\_\_\_\_ Date: \_\_\_\_\_


Invoice address:		Delivery address (if different)	
Company:			
Street:			
Zip-Code; City:			

Mounting in:  machine room  shaft


Type 8 ø200mm Va = 0,50 – 2,04 m/s

Type 7 ø300mm Va = 0,70 – 3,43 m/s

Type 9 ø300mm Va = 0,50 – 0,70 m/s



Standard installation (upright)



hanging version 180°

Tripping speed VA:

Nominal speed VN:

*Deviating installation options must be requested SEPARATELY!*

**(Specification necessary for tripping speed from 1,50m/s)**

**Safety switch nominal speed <1,00m/s / tripping speed to 1,49m/s:**

safety switch (1NCC / 1NOC)	(1563)	no detent	<input type="checkbox"/>	(1564)	detent	<input type="checkbox"/>
safety switch (2NCC)	(1562)	no detent	<input type="checkbox"/>	(2500)	detent	<input type="checkbox"/>
safety switch (2NCC / 1 NOC)	(1571)	no detent	<input type="checkbox"/>			
safety switch electromagnetic resettable (2NCC / 1NOC)				(1475)	detent	<input type="checkbox"/>
safety switch depending on direction (1NCC / 1NOC)	(1563)	no detent	<input type="checkbox"/>	(1564)	detent	<input type="checkbox"/>

**Safety switch nominal speed >1,00m/s / tripping speed from 1,50m/s:**

safety switch as pre-cut off switch electromagnetic and mechanical resettable (1NCC)				(2230)	detent	<input type="checkbox"/>
safety switch as pre-cut off switch electromagnetic resettable (2NCC / 1NOC)				(2240)	detent	<input type="checkbox"/>
safety switch depending on direction (1NCC / 1NOC)	(1563)	no detent	<input type="checkbox"/>	(1564)	detent	<input type="checkbox"/>

**Additional options:**

hardened groove for catching upwards: <input type="checkbox"/>	test groove: <input type="checkbox"/>	crown tooth for sensor feeding : <input type="checkbox"/>		
<b>Anti-Creep Protection</b> 100% duty ratio incl. switch and holder	12V DC <input type="checkbox"/>	24V DC <input type="checkbox"/>	230V AC <input type="checkbox"/>	
<b>Remote release</b> 100% duty ratio incl. holder	12V DC <input type="checkbox"/>	24V DC <input type="checkbox"/>	230V AC <input type="checkbox"/>	110V AC <input type="checkbox"/>
<b>Cover</b> acc. to EN 81: <input type="checkbox"/>	<b>Cover</b> acc.to Industrial Safety R. (Full coverage) <input type="checkbox"/>	<b>Adapter plate:</b> <input type="checkbox"/>		
<b>Kit for momentum encoder</b> : Pressure on the existing belt:	1:2 (10mm) (114 XL) <input type="checkbox"/>	1:4 (6mm) (110 XL) <input type="checkbox"/>		

**Steel rope galvanized 6,5mm (DIN EN 12385-5)**

6x19-SFC-1770 N \_\_\_\_\_ Meter rope lock (per rope 2x)  wire rope clips (per rope 4x)