

6.0**REQUEST data sheet****Tension weights / Substructure**

Version 20-01

BODE
COMPONENTS

Request No. _____

Date: _____

Delivery date: _____

Quantity: _____

Invoice address:		Delivery address (if different)
Company:		
Street:		
Zip code/ City:		

Tension weights for installation on the guiding rail:

(Incl. slack rope switch and cover according to EN 81)

- Type SRV 200mm 300mm catch in downwards direction incl. 15kg weight:
(Picture No. 1)
- Type SR/FO-V* 200mm 300mm catch in up- and downwards direction incl. 30kg weight:
(Picture No. 2)
- Type SGI-S* 200mm 300mm catch in up- und downwards direction incl. integrated pulley and 65kg weight:
(Picture No. 3) (without cover because of integrated pulley)

Tension weights for installation on the bottom of the shaft for catching in up- and downward direction:

(incl. slack rope switch according to EN 81)

- Type SGI* 200mm 300mm incl. integrated pulley and 65kg weight:
(Picture No. 4)
- Type SGD* as duplex guiding stand incl. pulley with bearing stand and 75kg weight:
(Picture No. 5)

Substructure with auxiliary emergency switch and spiral springs

- Substructure 300mm Type 7 up to VA 1,49m/s 500mm
- Substructure 300mm Type 7 from VA 1,50m/s 1500mm*
- Substructure 200mm Type 8 up to VA 1,50m/s 500mm

SRV (15 kg)
(Picture No. 1)SRFO* (30 kg)
(Picture No. 2)SGI-S* (65 kg)
(Picture No. 3)SGI* (65 kg)
(Picture No. 4)SGD* (75 kg)
(Picture No. 5)

* The delivery of these tension weights and substructures is possible only on a pallet with a freight carrier.